

EDRAWER4060J-S3



FEATURES

- 4U with 60x top-load 12G SAS patented tray-less hot-swap HDD bays
- Hot-swap redundant 12G Expanders up to 192Gbps per Expander
- 32" short depth with patented internal cable-management-arm
- Ease of serviceability with 6 hotswap exhaust fans and Platinum grade HRP PSU
- Remote management GbE port for status report

SPECIFICATIONS

Storage Controller	Single or Dual Redundant expanders; Each expanders with two 12G LSI SAS3X48
I/O Interface	Each expander has 4x 12Gbps SAS SFF8644 for Uplink and 4x 12Gbps SAS SFF8644 for Down-link
Controller Support	6 or 12Gb/s Host-based SAS RAID or HBAs with external connectivity
Storage	60x 3.5" 12Gbps/6Gbps SAS or SATA HDD bays Patented Trayless drive bay design
Cooling	Six 97mm redundant hot-swap exhaust fan modules with smart fan control
Enclosure Management	HDD Status/Identifier LEDs, Smart Fan, Thermal Monitor, HDD Monitor, Voltage Monitor, Inband SES Support
Power	1+1 Redundant 1200W AC 80plus Platinum high efficiency power supplies; DC option available



Backplane	Three 20 bays 12G SAS dual ported backplanes
Other Features	3 individual 20bay drawers for easy serviceability Patented internal cable-management-arm without rear cable-management-arm
Weight	Gross Weight: 80lbs without Hard Drives Net Weight: 70lbs without Hard Drive
Dimensions	System: 32"x19"x7" (LxWxH) Packaging: 48"x25"x27" (LxWxH) palletized
HTS Code	8473 30 5100
ECCN	4A994
Environmental	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
Compliance	CE, FCC Class A, RoHS 6/6 compliant

ORDERING INFO

JB4CDAD021	EIS SAS 12G 4U60 dual ports JBOD, Dual expander, 1600W AC HRP
JB4CDAS021	EIS SAS 12G 4U60 dual ports JBOD, Single expander, 1600W AC HRP

