

eDRAWER4048J-S3



FEATURES

- 4U with 48x top-load 12G SAS/SATA hot-swap trayless bays
- Support total 12x SFF8644 ports for up to 256Gbps of SAS bandwidth to Host and Expansion connections
- Dual 12G SAS expander modules supporting 12G SAS devices and EDFB for 6G SATA device
- 1100W FAN+PSU modules with individual hot-swappable fan modules



SPECIFICATIONS

Supported Expander	Two LSI SAS 12Gbps Expander
I/O Expansion	8x 12Gbps SAS SFF8644 for Uplink 4x 12Gbps SAS SFF8644 for Downlink
Controller Support	12 & 6Gb/s Host-based RAID Controller cards and HBAs with external connectivity
Storage	48x 3.5" 12/6Gbps SAS/SATA Trayless bays
Cooling	Six 80mm hot-swap exhaust fan modules with Smart Fan Control for optimal cooling
Enclosure Management	Web GUI Ethernet Mgmt Port, HDD Status/ Identifier LEDs, Smart Fan, Thermal Monitor, HDD Monitor, Voltage Monitor, Inband SES3 Support
Power	1+1 1100W AC/DC high efficiency redundant power supplies

Backplane	Two 24-Bay 12G SAS dual-ported backplanes
Gross Weight	108lbs w/o Hard Drives
Dimension	System: 29"x19"x7" (LxWxH) Packaging: 45.5"x 25"x23" (LxWxH) palletized
HTS Code	8473 30 5100
ECCN	4A994
Environmental	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
Compliance	CE, FCC Class A, RoHS 6/6 compliant

ORDERING INFO

BBHP44802A	EIS SAS 12G 4U48 dual ports JBOD, Dual expander, 1100W AC HRP
BBHP448A2A	EIS SAS 12G 4U48 dual ports JBOD, Single expander, 1100W AC HRP

