

EDRAWER4072J-S3



FEATURES

- 4U with 72x top-load 12G SAS/SATA hot-swap trayless bays
- "Support total 12x SFF8644 ports for up to 384Gbps of SAS bandwidth to Host and Expansion connections"
- "Dual 12G SAS expander modules supporting 12G SAS devices and EDFB for 6G SATA devices"
- 1100W FAN+PSU modules with individual hot-swappable fan modules

SPECIFICATIONS

Supported Expander	Two LSI SAS 12Gbps Expander
I/O Expansion	"8x 12Gbps SAS SFF8644 for Uplink 4x 12Gbps SAS SFF8644 for Downlink"
Controller Support	"12 & 6Gb/s Host-based RAID Controller cards and HBAs with external connectivity"
Storage	72x 3.5" 12/6Gbps SAS/SATA Trayless bays
Cooling	Six 80mm hot-swap exhaust fan modules with Smart Fan Control for optimal cooling
Enclosure MGMT	"Web GUI Ethernet Mgmt Port, HDD Status/ Identifier LEDs, Smart Fan, Thermal Monitor, HDD Monitor, Voltage Monitor, Inband SES3 Support"



Power	1+1 1100W AC/DC high efficiency redundant power supplies
Backplane	Three 24-Bay 12G SAS dual-ported backplanes
Gross Weight	72lbs w/o Hard Drives
Dimension	"System: 36"x19"x7" (LxWxH) Packaging: 47.6"x 25"x23" (LxWxH) palletized"
HTS Code	8473 30 5100
ECCN	4A994
Environmental	"Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing"
Compliance	CE, FCC Class A, RoHS 6/6 compliant

ORDERING INFO

BBHP44802A	EIS SAS 12G 4U72 dual ports JBOD, Dual expander, 1100W AC HRP
BBHP448A2A	EIS SAS 12G 4U72 dual ports JBOD, Single expander, 1100W AC HRP

