

# OSS424-D5



## FEATURES

- Versatile 4U Storage chassis with optical cooling for high end server
- 24 tray-less hot Swap 3.5" HDD 6G/12G SAS or SATA drive bays
- Optional 2, 8, 10 hot-swap 2.5" 7mm drive bays rear accessible
- High efficiency Platinum redundant PSU 800W or 1200W
- Supports up to SSI EEB/TEB Extended ATX motherboard



## SPECIFICATIONS

<b>Processor Support</b>	Supports Dual Intel® Xeon® SP (Skylake) up to 205W TDP socket LGA3647
<b>Chipset</b>	Intel® C621 chipset
<b>Memory Support</b>	Supports 12x DDR4 RDIMM/LRDIMM (3DS) 2133/2400/2666 MT/s
<b>Expansion Slot</b>	Supports a total of 7 low profile expansion slots; 4x PCIe3 x16, 3x PCIe3 x8
<b>Storage</b>	36ports 12Gb/s SAS Expander with 3 SFF8643 ports
<b>Drive Bays</b>	24x SAS/SATA 12G/6G tray-less 3.5" bays, 2x internal OS 2.5", Optional: 2/8/10x Rear tool-less 2.5" 7mm bays
<b>Network</b>	2x GbE ports
<b>Power</b>	1+1 800W or 1200W Platinum Redundant PSU, optional -48V DC input available upon request

<b>Supported OS</b>	Windows 2012 R2, RHEL 6.5, SLES 11 SP3, Windows 2008 R2, VMWare ESXi 5.5, FreeBSD 9.2 Centos 6.5; For other OS, please contact us.
<b>Front Panel</b>	Power On/Off with LED, Reset switch, NMI switch, Locate switch with LED, 4x LAN LED, Status/Warning LED
<b>Rear I/O</b>	4x USB 3.0; 1x D-Sub 15-pin VGA port; 2x RJ-45 GbE ports
<b>Cooling</b>	3x 120mm fans
<b>Other Features</b>	RAID 0/1/10/5 (Intel RSTe)
<b>Weight</b>	Gross: 37.5KG/82.5lbs Net: 15.9KG/35lbs
<b>Dimensions</b>	System: 26"x19"x7" (LxWxH) Packaging: 37"x25.2"x21.6" (LxWxH)
<b>Logistic</b>	HTS Code: 8473 30 5100; ECCN: 4A994
<b>Environmental</b>	Operating Temperature: 0°C to 35°C Non-Operating Temperature: -20°C to 70°C Humidity: 5% to 95% non-condensing
<b>Compliance</b>	CE, FCC Class A, RoHS 6/6 compliant

## ORDERING INFO

BB42433D5TY16-A 4U 24 BAYS 3.5" HDD 12G SAS DUAL XEON SP 800W HRP

