



In-Vehicle Computer

ACO-6000-KBL-16XM12

Surveillance Applied Computer with 6th/7th Gen Intel® Core™ Processor and Q170 PCH, 2x LAN, 16x M12 LAN



Features


- LGA 1151 socket for 6th /7th Gen. Intel® Core™ i7/i5/i3 or Pentium® / Celeron® Desktop Processor
- Intel® Q170 Chipset
- 2x 260-pin DDR4 SODIMM. Max up to 32GB
- Triple independent display supported by 1x DVI-I and 2x DisplayPort
- 2x Intel® GbE supporting Wake-on-LAN and PXE
- 16x Intel® GbE with M12 connector
- 4x 2.5" SATA HDD bay and 2x mSATA supporting RAID 0, 1, 5, 10
- 3x Full-size mini PCIe for communication or expansion modules, 3x SIM socket
- 5x RS-232/422/485 (w/ 3x internal), 6x USB 3.0, 2x USB 2.0 (internal)
- 8x DI + 8x DO with Isolation
- 2x Universal Bracket (For mini PCIe application)
- 9 to 48VDC wide range power input supporting AT/ATX mode
- -25°C to 70°C extended operating temperature
- Power ignition management

Specifications

System		Operating System	
Processor	Support 6th & 7th Gen Intel® Core™ i7 / i5 / i3 / Pentium® / Celeron® Desktop Processor (LGA 1151)	Windows	6th Gen CPU: Windows 10, Windows 7, WES7 7th Gen CPU: Windows 10
	<ul style="list-style-type: none"> • 7th Gen Intel® Core™ i7-7700T, Quad Core, 8MB cache, up to 3.8 GHz • 7th Gen Intel® Core™ i5-7500T, Quad Core, 6MB cache, up to 3.3 GHz • 7th Gen Intel® Core™ i3-7101TE, Dual Core, 3MB Cache, 3.4 GHz • 6th Gen Intel® Core™ i7-6700TE, Quad Core, 8MB Cache, up to 3.4 GHz • 6th Gen Intel® Core™ i5-6500TE, Quad Core, 6MB Cache, up to 3.3 GHz • 6th Gen Intel® Core™ i3-6100TE, Dual Core, 4MB Cache, 2.7 GHz • Intel® Pentium® G4400TE, Dual Core, 3MB Cache, 2.4 GHz • Intel® Celeron® G3900TE, Dual Core, 2MB Cache, 2.3 GHz 	Linux	Linux kernel 4.X
System Chipset		Power	
System Chipset	Intel® Q170 Express Chipset	Power Adapter	220W, AC/DC 24V/5A
LAN Chipset	<ul style="list-style-type: none"> • GbE1: Intel® I210-AT (Support Wake-on-LAN and PXE) • GbE2: Intel® I219LM (Support Wake-on-LAN and PXE) • GbE3~GbE18: Intel® I350-AM4 	Power Mode	AT, ATX
Audio Codec	Realtek ALC888S	Power Supply Voltage	9 ~ 48 VDC
System Memory	2x 260-Pin DDR4 1866/2133MHz SODIMM. Max. up to 32GB	Power Connector	3-pin Terminal Block
BIOS	AMI 128Mbit SPI BIOS	Power Protection	Over-Voltage Protection (OVP) Over-Current Protection (OCP) Reverse Polarity Protection (RPP)
Watchdog	Software Programmable Supports 1~255 sec. System Reset	Environment	
TPM	TPM 1.2	Operating Temperature	-13°F ~ 158°F (-25°C ~ 70°C)
Display		Storage Temperature	-22°F ~ 185°F (-30°C ~ 85°C)
Display Port	2x DP	Relative Humidity	10% to 95% (non-condensing)
DVI	1x DVI-I	Certification	CE, FCC Class A, E-Mark, EMC Conformity with EN50155 & EN50121-3-2
Multiple Display	Triple Display	Vibration	5 Grms, 5 ~ 500 Hz, 0.5 hr/axis (SSD) 1 Grms, 5 ~ 500 Hz, 0.5 hr/axis (HDD)
Storage		Shock	50G, half-sine, 11 ms (SSD)
mSATA	2x mSATA (shared by 2x Mini PCIe)	Physical	
SIM Socket	2x External SIM socket 1x Internal SIM Socket	Dimensions	240 (W) x 261 (D) x 100 (H) mm
SSD/HDD	2x Internal 2.5" SATA HDD Bay 2x Hotswap 2.5" SATA HDD Bay Support RAID 0, 1, 5, 10	Weights	5.34 ~6.82 kg
		Construction	Extruded aluminum with heavy duty metal
		Mounting Options	Wall Mount
Expansion			
Mini PCIe	3x Full-size Mini PCIe		
Expansion Modules			
4-port GbE module with Intel® I350-AM4 Chipset, RJ-45 or M12 connector (PoE optional)			
I/O			
Audio	1x Mic-in, 1x Line-out		
COM	5x RS-232/422/485		
DIO	8 in / 8 out (Isolated)		
LAN	2x GbE RJ45 16x GbE M12 (Module)		
PoE	16x IEEE 802.3at (25.5W) GbE M12 (Module)		
Universal I/O Bracket	2x Universal I/O Bracket (Base Model)		
USB	6x USB 3.0, 2x USB 2.0		
Others	6x WiFi Antenna Holes 1x Power Switch (front), 1x AT/ATX Switch (front) PC/Vehicle Mode, Vehicle Voltage, Delay Off Time (front) 1x Remote Power On/Off (rear)		


* All specifications and photos are subject to change without notice.

External I/O Mechanical Layout



Dimension

Unit: mm



Available Models

Model No.	Description
ACO-6000-KBL-16L-M12-P	In-Vehicle Computer with 7th Gen Intel® Core™ Processor and Q170 PCH, 2x LAN, 16x M12 LAN
ACO-6000-KBL-16P-M12-P	In-Vehicle Computer with 7th Gen Intel® Core™ Processor and Q170 PCH, 2x LAN, 16x M12 PoE LAN

Optional Accessories

Model No.	Description
1-E09A22801	Adapter AC/DC 24V/11.67A 280W with 3pin Terminal Block Plug 5.0mm Pitch
1-E09A22102	Adapter AC/DC 24V 9.2A 220W with 3pin Terminal Block Plug 5.0mm Pitch
999930	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm

Packing List

- 1x ACO-6000-KBL-16XM12
- 1x Utility DVD Driver
- 1x Wall Mount Kit
- 1x Accessory Kit

Exports And Tariff Codes

ECCN	5A992.c
HTS	8471.50.0150
Schedule B	84.71