



## CT-MBL01

MicroATX Industrial Motherboard with LGA 1700 for Intel® Core™ Series 2/14th/13th/12th Gen Processors, Q670E PCH



## Features

- Support Intel® Core™ Series 2/14th/13th/12th Gen Processors
- Intel® Q670E chipset
- 4x DDR5 4400 MT/s UDIMM, up to 128GB
- 1x 1GbE, 1x 2.5GbE (Support Wake-on-LAN and PXE)
- 4 independent display supported DP++
- 1x PCIe x16 (Gen 5), 2x PCIe x4 (Gen4, Gen3), 1x PCIe x16 (Gen 4)
- 2x M.2 (M Key, NVMe PCIe x4, SATA, 2242/2260/2280); 1x M.2 (E Key, PCIe x2, USB 2.0, 2230)
- 6x RS-232/422/485, 2x USB 3.0 Gen 1, 4x USB 2.0 Internal header, 6x USB 3.1
- 4x SATA 6.0Gb/s
- TPM 2.0

## Specifications


System	
Processor	Intel® Core™ Series 2 (Bartlett Lake-S) and 12th/13th/14th Gen Intel® Core™ i9/i7/i5/i3 processors (LGA1700, up to 65W TDP)
System Chipset	Intel® Q670E Chipset
LAN Chipset	GbE1: Intel® I226LM, 1GbE (Support Wake-on-LAN and PXE) GbE2: Intel® I226-V, 2.5GbE (Support Wake-on-LAN and PXE)
Audio Codec	Realtek ALC888S HD Audio Codec, support 5.1 channel
System Memory	4x DDR5 4400 MT/s UDIMM, up to 128GB
Graphics	Intel® Integrated Iris Xe Graphic (CPU Dependent)
BIOS	AMI uEFI 256MB SPI flash
Watchdog	Software Programmable Supports 1~255 sec. System Reset
iAMT	Intel® AMT 12.0 supported
TPM	TPM 2.0
Display	
Display Port	4x DP++ (4096 x 2304)
Multiple Display	Quad Display
Storage	
M.2	1x M.2 M/ NVMe PCIe x4 Gen 4/ 2242, 2260, 2280 1x M.2 M/ NVMe PCIe x4 Gen 4/ SATA/ 2242, 2260, 2280 1x M.2 E/ PCIe x2 Gen 3/ USB 2.0/ 2230
SATA	4x SATA
Expansion	
PCIe	1x PCIe x16 Slot (Gen 5) 1x PCIe x16 Slot (Gen 4, 4-Lane) 1x PCIe x4 Slot (Gen 4, Open End) 1x PCIe x4 Slot (Gen 3, Open End)
I/O	
Audio	1x Mic-in, 1x Line-in, 1x Line-out
USB	6x USB 3.1 Gen 2 (10 Gbps) 1x USB 3.2 Gen 2x2 (20 Gbps) Type C
Internal I/O	
Audio	1x Front panel audio
COM	6x RS-232
DIO	1x 8-bit DIO (4-in/4-out)
SATA	4 x SATA Gen 3, support RAID 0/1/5/10)
USB	2x USB 3.0 Gen 1 4x USB 2.0
Others	1x SPI header 1x Front panel 1x CPU fan 2x System fan
Operating System	
Windows	Windows 10/11 IoT Enterprise LTSC
Linux	Linux Kernel 5.X
Power	
Power Adapter	ACPI 5.0 compliant
Power Mode	ATX Power
Power Connector	2x12-pin and 2x2-pin power connector
Mechanical & Environment	
Form Factor	MicroATX
Operating Temperature	0 °C to 60 °C
Storage Temperature	-40 °C to 85 °C
Relative Humidity	10% ~ 90% relative humidity, non-condensing

Certification	CE, FCC Class B
---------------	-----------------

## Physical


Dimensions	244mm x 244mm
------------	---------------

External I/O Mechanical Layout



Dimension

Unit: mm



## Compliances and Standards

Shock	IEC60068-2-27:2008 Designed to comply with MIL-STD-810H Method 516.8 Procedure I
Vibration	IEC60068-2-64:2008 Designed to comply with MIL-STD-810H Method 514.8 Procedure I
Operating Temperature	0 °C to 60 °C IEC60068-2-1:2007 (Cold test procedure) IEC60068-2-2:2007 (Dry heat test procedure) IEC60068-2-3:2007 (Damp heat, steady state, test procedure) IEC60068-2-14:2009 (Wide temperature range thermal shock)
EMI	<ul style="list-style-type: none"> <li>• FCC Class B</li> <li>• CE</li> <li>• ICES-003</li> <li>• UKCA</li> </ul>

## Available Models

Model No.	Description
CT-MBL01	MicroATX Industrial Motherboard with LGA 1700 for Intel® Core™ Series 2/14th/13th/12th Gen Processors, Q670E PCH

## Packing List

1x CT-MBL01  
1x SATA cable  
1x I/O port bracket

## Exports And Tariff Codes

ECCN	5A992.c
HTS	8504.90.2000
ScheduleB	8473.30.0002

### Premio Inc.

918 Radecki Ct., City of Industry  
CA 91748, United States  
Toll Free: 800.977.3646

### Premio Taiwan Inc.

18F, No.176, Jianyi Road, Zhonghe District,  
New Taipei City 235603, Taiwan  
Toll Free: 886.2.7731.7888

Email: [sales@premioinc.com](mailto:sales@premioinc.com)  
Website: <https://premioinc.com>