



# S10-W224-8365UE

24" 16:9 FHD Resistive / Capacitive Touch Stainless Steel Panel PC with Intel® Core™ i5-8365UE Processor



**FEATURES**

- 24" Full HD 16:9 LCD with resistive 5-wire / projected capacitive touch Intel® Core™ i5-8365UE Processor, 4.10 GHz
- 1x DDR4 2400MHz SO-DIMM memory slot, 1x mSATA slot for internal storage
- 1x M12 for 2x USB 2.0, 1x M12 for LAN, 1x M12 for COM
- 1x Full-size Mini PCIe for expansion
- Support 110V to 240V AC power input by M12 Power Connector
- -10°C to 50°C operating temperature
- Full system IP66/IP69K with Stainless Steel SUS316 construction
- Touch Function ON/OFF Switch


**SPECIFICATIONS**

<b>Display</b>	
LCD Size	23.8" [16:9]
Max Resolution	1920 x 1080 (FHD)
Brightness	300 / 1000 (Optional)
Contrast Ratio	1,000:1
LCD Color	16.7M
Pixel Pitch (mm)	0.248 (H) x 0.248 (V)
Viewing Angle (H-V)	178 / 178
Backlight MTBF	50000 hrs (LED Backlight)
<b>Touch</b>	
Resistive 5-Wire	For S10-W224R-8365UE
Projected Capacitive	For S10-W224C-8365UE
<b>System</b>	
Processor	Intel® Core™ i5-8365UE Processor 6M Cache, up to 4.10 GHz
System Chipset	SoC integrated
LAN Chipset	GbE2: Intel® I210-IT (Support Wake-on-LAN and PXE)
Audio Codec	Realtek ALC888S HD Audio Codec
System Memory	1x 260-Pin DDR4 2400MHz SO-DIMM slot, Max 32GB
BIOS	AMI uEFI 256MB SPI flash
Watchdog	Software Programmable Supports 1~255 sec. System Reset
<b>Storage</b>	
mSATA	1x mSATA slot for internal storage
SIM Socket	1x Internal SIM socket
<b>Expansion</b>	
Mini PCI Express	1x Full-size Mini PCIe
<b>Other Features</b>	
OSD	OSD: Power On/Off, Reset Touch: On/Off switch
<b>I/O</b>	
COM	1x RS-232/422/485 by M12 A-Code 8-pin
USB	2x USB 2.0 by M12 A-code 8-pin
LAN	1x LAN by M12 X-Code 8-pin
Others	1x Additional RS-232/422/485 by M12 A-Code 8-pin 2x Additional USB 2.0 by M12 A-Code 8-pin 1x Additional LAN by M12 X-Code 8-pin 2x WiFi Antenna

<b>Operating System</b>	
Windows	Windows 10
Linux	Linux kernel 3.X
<b>Power</b>	
Power Mode	ATX
Power Supply Voltage	110 ~ 240V AC Input Optional 12V DC Input
Power Connector	M12 A-code 4-pin
Power Adapter	Optional AC/DC 12V/5A, 60W
<b>Environment</b>	
Operating Temp.	-10°C to 50°C
Storage Temp.	-20°C to 70°C
Relative Humidity	10%~80% (non-condensing)
IP Level	Full System IP66/IP69K
Vibration	With SSD: 2.4 Grms, 5 - 500 Hz, 0.5 hr/axis With HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis
Shock	With SSD: 20G, half sine, 11ms
Certifications	CE, FCC Class A
<b>Physical</b>	
Construction	Stainless Steel SUS316
Dimension	TBD
Weight	TBD
Mounting	VESA Mounting Holes 100 x 100mm or 200 x 100mm Optional Yoke Mount, Panel Mount

\* All specifications and photos are subject to change without notice

## EXTERNAL I/O MECHANICAL LAYOUT



## AVAILABLE MODELS

MODEL NO.	DESCRIPTION
SIO-W224R-8365UE	23.8" 16:9 FHD Resistive Touch Stainless Steel Panel PC with Intel® Core™ i5-8365UE Processor
SIO-W224C-8365UE	23.8" 16:9 FHD Capacitive Touch Stainless Steel Panel PC with Intel® Core™ i5-8365UE Processor
SIO-W224HR-8365UE	23.8" 16:9 FHD HB 1000nits Resistive Touch Stainless Steel Panel PC with Intel® Core™ i5-8365UE Processor
SIO-W224HC-8365UE	23.8" 16:9 FHD HB 1000nits Capacitive Touch Stainless Steel Panel PC with Intel® Core™ i5-8365UE Processor

## OPTIONAL ACCESSORIES

MODEL NO.	DESCRIPTION
1-TPWR00027	Waterproof AC Power Input M12 A-CODE 4P PWR Cable to Plug Type_US L=3M
1-TPWR00028	Waterproof AC Power Input M12 A-CODE 4P PWR Cable to Plug Type_EU L=3M
1-TUSB00034	Waterproof USB 2.0 Cable 3M
1-TCOM00019	Waterproof COM Cable 3M
1-TLAN00015	Waterproof LAN Cable 3M

## PACKING LIST

- 1x SIO-W224 Series Stainless Steel Panel PC
- 1x Utility DVD Driver
- 1x Waterproof Connector Cover Set