



FANLESS MINI COMPUTER

BCO-1000-ADLN_2L

Fanless Mini Computer with 12th Gen Intel® IoTG N97 Processor, 1x DP, 1x HDMI, 2x COM, 2x LAN, 1x 2.5" Drive Bay

Features

- Support 12th Gen Intel® IoTG Alder Lake-N Processor N97, QC, 12W
- DDR5 4800 MT/s SO-DIMM. Max. 16GB
- Dual Independent Display by 1x Display Port, 1x HDMI
- 2x 2.5GbE LAN
- 1x 2.5" SSD Drive Bay
- 1x M.2 B-Key (Default: 128GB SSD)
- 2x COM, 2x USB 3.2 Gen2, 2x USB 3.2 Gen1, 2x USB 2.0
- 9 to 36VDC Wide Range Power Input Supporting AT/ATX Mode
- Wide Operating Temperature 0°C to 50°C
- TPM 2.0 Supported
- CE, FCC Class A




Specifications

System		Physical	
Processor	Support 12th Gen Intel® IoTG Alder Lake-N Processor N97, QC, 12W	Dimensions (WxDxH)	192 x 140 x 68mm
System Chipset	SoC integrated	Construction	Extruded Aluminum with Heavy Duty Metal
LAN Chipset	2x Intel® I225-V 2.5GbE LAN	Mounting Options	Wall Mounting DIN-Rail Mounting (Optional)
Audio Codec	Realtek ALC897		
System Memory	DDR5 4800 MT/s SO-DIMM. Max. 16GB		
Graphics	Intel® UHD Graphics		
BIOS	AMI UEFI BIOS		
Watchdog	Software Programmable Supports 1~255 sec. System Reset		
TPM	TPM 2.0		
Display			
Display Port	1x DisplayPort 1.4a Max Resolution 4096 x 2304 @60Hz		
HDMI	1x HDMI 1.4b Max Resolution 3840 x 2160 @30Hz		
Multiple Display	2x Independent Displays		
Storage			
M.2 B-Key	1x M.2 B-Key slot (2242/2280/3042) • Supports 1x PCIe x1 SATA signal, (Default 128GB SSD) • Supports B+M Key SSD		
SATA	1 x 2.5" Drive Bay (7mm or 9mm)		
Expansion			
M.2 E-Key	1x M.2 E-Key (2230) • Support PCIe x1 & USB 2.0; Support CNVi • Devices Supported: Intel® AX210 Wi-Fi & BT (vPro Supported)		
I/O			
Audio	Line-in/Line-out/Mic-in		
COM	2x DB9 COM1: RS232/422/485 COM2: RS232		
GPIO	1x 8 GPIO		
LAN	2x RJ45 (2.5GbE)		
USB	2x USB 3.2 Gen2 2x USB 3.2 Gen1 2x USB 2.0 Type-A		
Others	• 2x Antenna Holes • 1x Power button • 1x HD LED • 1x Power LED		
Operating System			
Windows	Windows 10/11		
Linux	Linux Kernel		
Power			
Power Adapter	Optional AC/DC 12V/5A, 60W		
Power Mode	AT, ATX (Default ATX)		
Power Supply Voltage	9~36VDC		
Power Connector	3-pin Terminal Block		
Environment			
Operating Temperature	0°C to 50°C (12W CPU)		
Storage Temperature	-30°C to 85°C		
Relative Humidity	10% to 95% (non-condensing)		
Certification	CE, FCC Class A		
Vibration	With SSD: 5 Grms (5 - 500 Hz, 0.5 hr/axis)		
Shock	With SSD: 50G half-sin 11ms		


* All specifications and photos are subject to change without notice.

External I/O Mechanical Layout



Dimension

Unit: mm



Compliances and Standards

Vibration	With SSD: 5 Grms (5 - 500 Hz, 0.5 hr/axis) IEC60068-2-64:2008 Designed to comply with MIL-STD-810H Method 514.8 Procedure I
Shock	With SSD: 50G half-sin 11ms IEC60068-2-27:2008 Designed to comply with MIL-STD-810H Method 516.8 Procedure I
Operating Temperature	0°C to 50°C (12W CPU) IEC60068-2-1:2007 (Cold test procedure) IEC60068-2-2:2007 (Dry heat test procedure) IEC60068-2-3:2007 (Damp heat, steady state, test procedure) IEC60068-2-14:2009 (Wide temperature range thermal shock)
EMC	• FCC Class A • CE • ICES-003 • UKCA • Industrial EMC Compliance - EN 61000-4-2: 2009 - EN IEC 61000-4-3: 2020 - EN 61000-4-4: 2012 - EN 61000-4-5: 2014 +A1: 2017 - EN 61000-4-6: 2014

Available Models

Model No.	Description
BCO-1000-ADLN97-2L-P	Fanless Mini Computer With 12th Gen Intel® IoTG N97 Processor, 1x DP, 1x HDMI, 2x COM, 2x LAN, 1x 2.5" Drive Bay, w/ Power Adapter

Optional Accessories

Model No.	Description
1-E09A06008	Adapter AC/DC 12V 5A 60W with 3pin Terminal Block Plug 5.0mm Pitch
1-TPCD00005	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm
3-DINR-0004	Din Rail-2 Mounting Kit

Packing List

1x BCO-1000-ADLN Fanless Mini Computer
1x Wall Mount Kit
1x Accessory Kit

US Exports And Tariff Codes

ECCN	5A992.c
HTS	8471.50.0150
ScheduleB	84.71

Premio Inc.

918 Radecki Ct., City of Industry
CA 91748, United States
Toll Free: 800.977.3646

Premio Taiwan Inc.

18F, No.176, Jianyi Road, Zhonghe District,
New Taipei City 235603, Taiwan
Toll Free: 886.2.7731.7888

Email: sales@premioinc.com
Website: <https://premioinc.com>