



AI EDGE INFERENCE COMPUTER

RCO-6000-CML-2-2B15M

AI Edge Inference Computer W/ LGA 1200 for Intel 10th Gen CPU & W480E PCH, 2x LAN, 2x 15mm HDD, 1x PCIe x16, 1x PCI

Features


- LGA 1200 socket for 10th Gen. Intel® CML S Processor (35W TDP)
- Intel® W480E chipset
- 2x DDR4 2666/2933MHz SODIMM. Max. up to 64GB
- Triple Independent Display: 2x DisplayPort, 1x DVI-I
- 2x Intel® GbE supporting Wake-on-LAN and PXE
- 2x Full-size Mini PCIe for communication or expansion modules, 2x SIM socket
- 5x 2.5" SATA HDD Bay (1x Internal) and with RAID 0, 1, 5, 10 support
- 1x M.2 (E Key, PCIe x1, USB 2.0, 2230)
- 8x RS-232/422/485 (6x internal), 6x USB 3.2 Gen 2, 3x USB 3.2 Gen 1 (1x internal)
- 8x DI + 8x DO with isolation
- 9 to 48VDC Wide Range Power Input Supporting AT/ATX Mode
- Wide Operating Temperature -25°C to 70°C (35W CPU)
- TPM 2.0 Supported
- Edge AI Ready with Hailo-8™ (26 TOPS / 2.5W)
- UL Listed




Specifications

System		Operating System	
Processor		Windows	Windows 10/11
Support 10th Gen Intel® CML S Processor (LGA 1200, 35W TDP)		Linux	Linux kernel
- Intel® Xeon® W-1290TE, 10 Cores, 20MB Cache, up to 4.5 GHz		Power	
- Intel® Core™ i9-10900TE, 10 Cores, 20MB Cache, up to 4.5 GHz		Power Adapter	Optional AC/DC 24V/5A, 120W Optional AC/DC 24V/9.2A, 220W
- Intel® Core™ i7-10700TE, 8 Cores, 16MB cache, up to 4.4 GHz		Power Mode	AT, ATX
- Intel® Core™ i5-10500TE, 6 Core, 12MB Cache, 3.7 GHz		Power Ignition Sensing	Power Ignition Management
- Intel® Core™ i3-10100TE, 4 Cores, 9MB Cache, up to 3.6 GHz		Power Supply Voltage	9~48VDC
System Chipset	Intel® W480E Chipset	Power Connector	5-pin Terminal Block
LAN Chipset	GbE1: Intel I219 (Support Wake-on-LAN and PXE) GbE2: Intel I210 (Support Wake-on-LAN and PXE)	Power Protection	OVP (Over Voltage Protection), OCP (Over Current Protection), Reverse Protection
Audio Codec	Realtek ALC888S	Environment	
System Memory	2x 260-Pin DDR4 2666 /2933MHz SODIMM. Max. up to 64GB (ECC and Non-ECC)	Operating Temperature	-25°C to 70°C (35W CPU)
Graphics	Intel® UHD Graphics 630	Storage Temperature	-30°C to 85°C
BIOS	AMI 256Mbit SPI BIOS	Relative Humidity	10% to 95% (non-condensing)
Watchdog	Software Programmable Supports 1~255 sec. System Reset	Certification	UL 62368 Ed. 3, CE, FCC Class A
AI Accelerator	Supports 4x Hailo-8™ modules	Vibration	With SSD: 5 Grms, 5 - 500 Hz, 0.5 hr/axis With HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis
TPM	TPM 2.0	Shock	With SSD: 50G, half sine, 11ms
Display		Physical	
Display Port	2x DisplayPort, support resolution 4096 x 2304, DP++	Dimensions	240 (W) x 261 (D) x 126.8 (H) mm
DVI	1x DVI-I, support resolution 1920 x 1200	Weights	5.7~5.85 kg
Multiple Display	Triple Display	Construction	Extruded Aluminum with Heavy Duty Metal
VGA	Yes (by optional split cable)	Mounting Options	Wall Mounting
Storage			
SIM Socket	2x External SIM socket (Mini PCIE attached)		
SSD/HDD	1x Internal 2.5" SATA/SSD HDD Bay (support H=9mm) 2x 7mm, 2x 15mm Hot-swappable 2.5" SATA HDD/SSD Bay Support RAID 0, 1, 5, 10		
Expansion			
M.2	1x M.2 (E Key, PCIe x1, USB 2.0, 2230)		
Mini PCIe	2x Full-size Mini PCIe		
PCIe	1x PCIe x16		
PCI	1x PCI		
Expansion Modules			
Occupied One Universal I/O Slot:			
• 4-port GbE module with Intel® I350 Chipset, RJ-45 or M12 connector (PoE optional)			
• 2-Port RJ45 10GbE with Intel X710 Chipset			
• 4-Port USB with Renesas uPD720201K8 host controller (share PCIe Gen2 x1 bandwidth)			
• 1x M.2 for 5G (B Key, PCIe x1, USB 3.0, 3042/3052), Including 2x SIM socket, 1x SIM switch (1x Universal Slot Only)			
Card Dimension	235 (L) x 112 (H) mm		
I/O			
Audio	1x Mic-in, 1x Line-out		
CAN	2x CAN 2.0 A/B 2-pin Internal header		
COM	2x RS-232/422/485 ; 6x RS-232/422/485 (internal)		
DIO	8 in / 8 out (Isolated)		
LAN	2x RJ45		
Universal I/O Bracket	2x Universal I/O Bracket (By mini PCIe interface)		
USB	6x USB 3.2 Gen 2 (10 Gbps) 3x USB 3.2 Gen 1 (5 Gbps, 1x Internal) 2x USB 2.0 header (internal)		
Others	5x WiFi Antenna Holes 1x Power Switch, 1x AT/ATX Switch, 1x Remote Power On/Off 1x PC/Car Mode Switch, 1x Delay Time Switch 1x Removable CMOS Battery 4x 4-Pin Power Connector, 1x 4-PIN FAN Connector		

External I/O Mechanical Layout




Available Modules



Dimension

Unit: mm





RCO-6000-CML-2-2B15M

Compatible GPU AVL

Model	GPU Memory	Memory Bandwidth	CUDA Cores	Tensor Cores	RT Cores	AI TOPS	Dimensions	Power & Thermal
RTX 4000 SFF Ada Generation	20GB GDDR6 ECC	320 GB/s	6144	192	48	307	2.7" x 6.6" LP DS	70 W
NVIDIA RTX 2000 Ada Generation	16 GB GDDR6 with ECC	224 GB/s	2816	88	22	192	2.7" x 6.6" LP DS	70 W
NVIDIA RTX A1000	8GB GDDR6	192 GB/s	2304	72	18	108	2.7" H x 6.4" LP SS	50 W

Compliances and Standards

Vibration	With SSD: 5 Grms, 5 - 500 Hz, 0.5 hr/axis With HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis IEC60068-2-64:2008 Designed to comply with MIL-STD-810H Method 514.8 Procedure I
Shock	With SSD: 50G, half sine, 11ms IEC60068-2-27:2008 Designed to comply with MIL-STD-810H Method 516.8 Procedure I
Operating Temperature	-25°C to 70°C (35W CPU) IEC60068-2-1:2007 (Cold test procedure) IEC60068-2-2:2007 (Dry heat test procedure) IEC60068-2-3:2007 (Damp heat, steady state, test procedure) IEC60068-2-14:2009 (Wide temperature range thermal shock)
EMC	• FCC Class A • CE • ICES-003 • UKCA • Industrial EMC Compliance - EN 61000-4-2: 2009 - EN IEC 61000-4-3: 2020 - EN 61000-4-4: 2012 - EN 61000-4-5: 2014 +A1: 2017 - EN 61000-4-6: 2014
Safety	• UL Safety: UL62368-1, 3rd Ed., (cULus) • Test procedure: CB Scheme • Standard: IEC 62368-1:2018

Available Models

Model No.	Description
RCO-6000-CML-2C-2B15M-P	AI Edge Inference Computer W/ LGA 1200 for Intel 10th Gen CPU & W480E PCH, 2x LAN, 1x PCIe x16, 1x PCI, 2 Bay 15mm, w/ Power Adapter

Optional Accessories

Model No.	Description
1-E09A12002	Adapter AC/DC 24V 5A 120W with 3pin Terminal Block Plug 5.0mm Pitch
1-E09A22102	Adapter AC/DC 24V 9.2A 220W with 3pin Terminal Block Plug 5.0mm Pitch
999930	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm

Packing List

1x RCO-6000-CML Series Embedded System
 1x Wall Mount Kit
 1x DVI to VGA Adapter

US Exports And Tariff Codes

ECCN	5A992.c
HTS	8471.50.0150
ScheduleB	84.71

Premio Inc.

918 Radecki Ct., City of Industry
 CA 91748, United States
 Toll Free: 800.977.3646

Premio Taiwan Inc.

18F, No.176, Jianyi Road, Zhonghe District,
 New Taipei City 235603, Taiwan
 Toll Free: 886.2.7731.7888

Email: sales@premioinc.com
 Website: <https://premioinc.com>